

## Scapa FR333

High Performance, Cold Weather Aluminium Tape - 40 micron

---

### DESCRIPTION

Scapa 333 is a 40 micron soft aluminium foil coated with a pressure sensitive acrylic adhesive system and a siliconised paper liner.

### APPLICATIONS

- Applications requiring detection by photoelectric equipment.
- Heat reflector.
- Closing rigid air duct insulation.
- Jointing and continuity of vapour barriers on external felting with aluminium sheathing.

### PRODUCT BENEFITS

- Temperature resistance: -35°C to +120°C.
- Same aluminium appearance as air duct.
- Easy to tear.
- Very soft and very conformable.

#### *Accreditation:*

*Meets the fire resistant requirements of specifications NF P 92 – 501, Fire Class M1, BS476 Part 6 & 7 Category 1, Class O and DIN4102-A2*

## TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Adhesion to Steel	6	N/cm	AFERA 5004
Elongation at Break	3	%	AFERA 5004
Tensile Strength	26	N/cm	AFERA 5004
Total Thickness	80	Microns	AFERA 5006

## STANDARD PRESENTATIONS

- Branding: Scapa,Barnier
- Core: 76mm
- Packaging: Bulk pack with Interleaving
- Roll Length: 50m
- Roll Width: 50mm, 75mm

## RECOMMENDATIONS

Rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. The storage temperature should be between +10°C and +25°C. Under these conditions, the storage life of the tape in a temperate climate will be at least 12 months.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.