



BARNIER ® 1253

Low Noise BOPP Packaging Adhesive Tape

DESCRIPTION

Scapa 1253 is a 28µ micron bi-axially oriented polypropylene film coated with a water based acrylic adhesive system, with 46 total thickness and recommended for general bundling and packaging applications.

APPLICATIONS

- Packing and closing cartons
- Pallet wrapping

PRODUCT BENEFITS

- Silent flow
- Good aging and good resistance to U.V.
- Not cold-breaking
- Moisture and chemical resistant.
- Applicable by hand or with Scapa HD209 or HD210 dispensers.
- Continuous temperature resistance: +60°C.

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Adhesion to Steel	2.1	N/cm	AFERA 5001
Elongation at Break	150	%	AFERA 5004
Tensile Strength	42	N/cm	AFERA 4004
Total Thickness	0.046	mm	AFERA 5006

Version: 12 Generated Date: 27 October 2025 Page: 1 of 2

www.scapaindustrial.com Product Code: 1253

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.

Note:

This will be taken from the core product for the SAP Material Group

STANDARD PRESENTATIONS

• Colours: Buff, Transparent and White

• Core: 76 mm Scapa branded cardboard core

• Packaging: Flat shrink pack

• Roll Length: 66, 100 and 132 metres

• Roll Width: 50 mm

RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +10°C and +30°C. Under these conditions, the storage life of the tape in a temperate climate will be at least one year.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.

 Version: 12
 Generated Date: 27 October 2025
 Page: 2 of 2

www.scapaindustrial.com Product Code: 1253