Technical DATA

Scapa 3160

Waterproof Cloth Tape - standard grade

DESCRIPTION

Scapa 3160 is a standard grade, polyethylene laminated, waterproof cloth tape, coated with a pressure sensitive natural rubber resin adhesive Scapa 3160 is available in black, white and silver.

APPLICATIONS

- Designed as an all purpose duct tape for general purpose applications.
- Used for sealing, bundling, short term masking and protecting.
- Excellent for jointing polyethylene sheeting in asbestos removal applications.
- Double glazing unit sealing.
- Medium temperature duct sealing within HVAC.
- Carpet joining and edging.

PRODUCT BENEFITS

- Good water resistance.
- Excellent adhesion and strength.
- Flexible and conformable.
- Easy tear.
- Good low temperature performance.
- Good all purpose product.
- Service temperature: -15°C to +75°C.

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Adhesion to Backing	3.0	N/cm	IEC 60454-2
Adhesion to Steel	5.0	N/cm	IEC 60454-2
Breaking Strength	35	N/cm	IEC 60454-2
Thickness	0.15	mm	AFERA 5006*

Note:

****This will be taken from the core product for the SAP Material Group****

STANDARD PRESENTATIONS

- Core: Cardboard
- Packaging: Bulk packed using interleaving sheets between layers./Shrink wrapped in packs of 4 *
- Roll Length: 25m, 50m
- Roll Width: 19mm, 25mm, 38mm, 50mm, 75mm, 100mm

Note:

Note: Information on stock items, non-standard sizes and colours, and lead times is available on request
**Dependant on size/colour combination*

RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging, until required for use. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Shelf life will vary with conditions of use and is affected by climatic environment, but under these conditions, it is recommended that this product should be used within two years from date of manufacture.

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.