



BARNIER ® 4472

Transfer adhesive

DESCRIPTION

Scapa 4472 FIX is an acrylic adhesive transfer tape 200 microns thick. It is reinforced by a polyester grid and protected by an 80 g / m2 siliconised paper liner.

APPLICATIONS

- mounting of rain shield or vapor barrier on uprights
- Grouting in excess thickness of vapor barrier and rainscreen films
- Permanent attachment to metal studs, galvanized steel or wood
- Fixing of all vapour barrier and sub-roof membranes, including Tyvek[®].

PRODUCT BENEFITS

- Very high tack
- Strong and permanent adhesion, to substrates with low surface energy such as Tyvek[®].
- Service temperature: -40°C to +120°C.

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Adhesion to Steel	24	N/25mm	AFERA 5001
Tack	<2	N/25mm	PSTC 6
Total Thickness (excluding liner)	200	Microns	AFERA 5006
Thickness of Liner	67	Microns	AFERA 5006

Note:

This will be taken from the core product for the SAP Material Group

 Version: 16
 Generated Date: 27 October 2025
 Page: 1 of 2

www.scapaindustrial.com Product Code: 4472

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.

STANDARD PRESENTATIONS

• Core: 76mm

Packaging: Bulk or shrink wrapped with one front label

Roll Length: 25 metresRoll Width: 19; 25 mm

RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature should be between +10°C and +30°C. Under these conditions, the storage life of the tape in a temperate climate will be 12 months.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants, before application. .

 Version: 16
 Generated Date: 27 October 2025
 Page: 2 of 2

www.scapaindustrial.com Product Code: 4472