

Scapa 6060

Plasticised PVC Adhesive

DESCRIPTION

Scapa 6060 is an embossed plasticised PVC film, coated in a rubber adhesive.

APPLICATIONS

- Multi-used building tape: repairing, sealing, masking, protection, securing tarpaulins
- Short-term masking on concrete, plaster, wood, metal, plastic for screening paintwork or render
- Interior and exterior use

PRODUCT BENEFITS

- Remains usable and supple even in low winter temperatures,
- Excellent sealing properties
- Good resistance to humidity
- Smooth application
- Easy to tear thanks to striation
- Thermal resistance up to 60°C.

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Total Thickness	155	µm	AFERA 5006
Adhesive Strength on Steel	1.0	N/cm	AFERA 5001
Breaking Load	24	N/cm	AFERA 5004
Elongation at Break	93	%	AFERA 5004

STANDARD PRESENTATIONS

- Roll Length: 33m
- Roll Width: 50mm
- Core: Neutral or SCAPA printed 76 mm cardboard roll
- Packaging: Individual with barcode
- Colours: White or yellow

RECOMMENDATIONS

The rolls should be stored flat, in their original packaging, protected against dust, light, moisture and solvent fumes, and at a temperature between +10°C and +30°C. Under these conditions, the period of storage of the rolls in a temperate climate may not exceed 12 months. Surfaces should be clean, dry and free of dust, grease, oil and or other contaminants. Owing to the variety of materials used by the user, a test carried out by the user themselves constitutes the most reliable way of testing the material before its actual application.