

BARNIER[®] CW30

High Performance, Cold Weather Aluminium Tape - 30 micron

DESCRIPTION

Scapa CW30 comprises a 30 micron, soft aluminium foil backing coated with cold weather acrylic based adhesive and supplied with a siliconised paper liner. This high performance aluminium tape is ideal for use in a range of demanding temperature and environmental conditions and provides good adhesive performance and water resistance

APPLICATIONS

- General purpose holding, patching, sealing and fixing applications.
- Joining of foil faced glass fibre or duct board joints.
- Sealing cold store insulation or double glazed units.
- For use as a vapour seal for sheet metal ducts.
- Closing rigid air duct insulation and shafts.
- Joining and sealing in HVAC applications.
- For use as a heat deflector.

PRODUCT BENEFITS

- Cold weather high quality adhesive for good bonding to a range of substrates
- Can be applied at low temperatures.
- Good high and low temperature resistance -service temperature: -35°C to +120°C.
- Good water vapour resistance.
- Same aluminium visual aspect to blend in easily with air ducts.
- Good ageing resistance both indoors and outdoors.
- Easy to tear for ease of use.
- Very soft and conformable.
- Aluminium backing provide good reflection of both heat and light.

Accreditation:

Meets the fire resistant requirements of specifications NF P 92 – 501, Fire Class M1, BS476 Part 6 & 7 Category 1, Class O and DIN 4102-part 1:B1

TECHNICAL PROPERTIES

| Technical Property | Nominal Value | Unit | Test Method |
|---------------------------|----------------|----------|-------------|
| Adhesion to Steel | 6 | N/cm | AFERA 5001 |
| Application Temperature | - 20°C + 40°C | °C to °C | - |
| Elongation at Break | 3 | % | AFERA 5004 |
| Service Temperature Range | - 35°C + 120°C | °C to °C | - |
| Tensile Strength | 20 | N/cm | AFERA 5004 |
| Total Thickness | 70 | Microns | AFERA 5006 |

STANDARD PRESENTATIONS

- Core: 76mm Scapa
- Packaging: Bulk packed
- Roll Length: 50m
- Roll Width: 50mm

RECOMMENDATIONS

Rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. The storage temperature should be between +10°C and +25°C. Under these conditions, the storage life of the tape in a temperate climate will be at least 12 months.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.