BARNIER ® 3162

Waterproof Cloth Tape - higher adhesion

DESCRIPTION

Scapa 3162 is a higher adhesion version, economy grade, polyethylene laminated waterproof cloth tape, coated with a pressure sensitive adhesive Scapa 3162 is available in black, white and silver.

APPLICATIONS

- All-purpose sealing and ventilation duct connection (indoors)
- Repairs
- Asbestos removal (polyethylene film fixation and bag closure)
- Fastening tarpaulins and holding cables
- Protection, masking
- Closing of containers and packaging

PRODUCT BENEFITS

- Good resistance and good sealing
- Flexible and conformable
- Flexible and conformable.
- Very good adhesion and immediate adhesive
- Operating temperature from -15° C to + 75 ° C

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Adhesion to Backing	3.5	N/cm	IEC 60454-2
Adhesion to Steel	6.0	N/cm	IEC 60454-2
Breaking Strength	35	N/cm	IEC 60454-2
Thickness	0.18	mm	AFERA 5006*

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.

Note:

****This will be taken from the core product for the SAP Material Group****

STANDARD PRESENTATIONS

- Core: Cardboard
- Roll Length: 25m, 50m
- Roll Width: 19mm, 25mm, 38mm, 50mm, 75mm, 100mm

Note:

** Dependant on size / colour combination Note: Information on stock items, non-standard sizes, and lead times is available on request*

RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging, until required for use. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Shelf life will vary with conditions of use and is affected by climatic environment, but under these conditions it is recommended the product should be used within two years from date of manufacture.

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.