

BARNIER® 6096FR

PVC Adhesive builders' tape for protection and reparation

DESCRIPTION

Scapa 6096 is PVC plasticized, coated with rubber adhesive. Scapa 6096 exists in grey and yellow

APPLICATIONS

- Repair, sealing, sealing, masking, protection, holding tarpaulins and masking films
- Formwork waterproofing (yellow)
- Short-term masking (less than 3 days) on concrete, plaster, metal, plastic

PRODUCT BENEFITS

- Sticks on all surfaces even when they are dusty or damp
- Easy unwind in spite of a very aggressive adhesive
- Easy tear
- Remains conformable and flexible, even at low temperatures in winter
- Masking with all types of paints
- High tack
- Water and humidity resistant and barrier
- Interior and exterior use

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Adhesion to Steel	1.2	N/cm	AFERA 4001
Elongation at Break	200	%	AFERA 4005
Operating Temperature	+70	°C	-
Tensile Strength	22	N/cm	AFERA 4004
Total Thickness	0.125	mm	AFERA 4006

STANDARD PRESENTATIONS

- Packaging: 36
- Dimension : 33mX50mm
- Core: 76mm
- Packaging (a): individual shrink with barcode

RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature should be between +10°C and +30°C. Under these conditions, the storage life of the tape in a temperate climate will be at least 12 months.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants. Because of the diversity of substrates used by the end user, the test conducted by the end user himself is the safest way to test the substrates before the final application.