



# **BARNIER ® 0485**

# Rubber Resin Adhesive Strip

## **DESCRIPTION**

Scapa 0485 is a solvent free rubber resin based hot melt adhesive. Scapa 0485 is available in amber in a strip format supplied on an easily removable paper liner.

#### **APPLICATIONS**

- Fixing on different materials: metal, wood, rigid plastics, polypropylene
- Collage on skirting boards, paneling, decorative rods, sill bars and electrical accessories (junction boxes, chutes)
- Polyane sheet connection in construction
- Maintaining parts before fixing deifnitive

#### **PRODUCT BENEFITS**

- Clean and easy application
- Excellent adhesive power
- Solvent-free adhesive

### **TECHNICAL PROPERTIES**

Technical Property	Nominal Value	Nominal Value Unit	
Cohesion	0.6	N/mm²	55270*
Service Temperature	0 - 40	ပ္	-
Softening Point (Ring and Ball)	85	ပ္	55272*
Specific Gravity	0.98	g/cm3	55295*
Tack (Rolling Ball Method)	30	mm	55233*

Version: 32 Generated Date: 23 October 2025 Page: 1 of 2

www.scapaindustrial.com Product Code: 0485

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.

N	n	+	0	
1 V	v	ι	C	٠

Note: should not be used where good chemical or UV resistance is required.

## **STANDARD PRESENTATIONS**

• Dimension: 10mx19mm

Packaging: 6Core: 76mm plain

Note:

Note: Information on stock items, non-standard sizes, and lead times is available on request

#### RECOMMENDATIONS

It is recommended that this product is applied at temperatures over 10°C.

To aid the cutting of 0485, it is advisable to dip blades or scissors into water immediately prior to use. The rolls should be stored flat on their cut edges in the original packaging, until required for use. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Service life will vary with conditions of use and is affected by climatic environment, but should not be less than one year from date of manufacture, if stored in a moderate climate and good conditions.

Version: 32 Generated Date: 23 October 2025 Page: 2 of 2

www.scapaindustrial.com Product Code: 0485

<sup>\*</sup> Scapa Internal Test Method.