



# **Scapa 1252**

## **BOPP Packaging Adhesive Tape**

### **DESCRIPTION**

Scapa 1252 is a 28 micron bi-axially oriented polypropylene film coated with a rubber based adhesive system, with 45µ total thickness and recommended for general bundling and packaging applications.

#### **APPLICATIONS**

- · Packing and closing cartons
- Pallet wrapping

#### **PRODUCT BENEFITS**

- High tack
- Solvent free.
- Moisture and chemical resistant.
- Applicable by hand or with Scapa HD209 or HD210 dispensers.
- Continuous temperature resistance: +50°C.

## **TECHNICAL PROPERTIES**

Technical Property	Nominal Value	Unit	Test Method
Adhesion to Steel	4.5	N/cm	AFERA 5001
Elongation at Break	170	%	AFERA 5004
Tensile Strength	39	N/cm	AFERA 5004
Total Thickness	0.045	mm	AFERA 5006

#### Note:

\*\*\*This will be taken from the core product for the SAP Material Group\*\*\*

 Version: 16
 Generated Date: 27 October 2025
 Page: 1 of 2

www.scapaindustrial.com Product Code: 1252

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.

#### STANDARD PRESENTATIONS

• Colours: Buff, Transparent and White

• Core: 76 mm Scapa branded cardboard core

• Packaging: Flat shrink pack

• Roll Length: 66, 100 and 132 metres

• Roll Width: 50 mm

Note:

Other widths may be available upon previous request and will be always subject to minimum order quantities

#### RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +10°C and +30°C.

Under these conditions, the storage life of the tape in a temperate climate will be at least one year. Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.

Version: 16 Generated Date: 27 October 2025 Page: 2 of 2

www.scapaindustrial.com Product Code: 1252