



# **Scapa 2900**

# Non Adhesive Hazard Warning Polyethylene Tape

# **DESCRIPTION**

Scapa 2900 is a  $25\mu m$  low density polyethylene film red and white striped and recommended for hazard warning and safety applications.

#### **APPLICATIONS**

• Hazard warning and safety non adhesive tape.

#### **PRODUCT BENEFITS**

- Easy to tie by hand.
- Suitable for indoor and protected outdoor environments.
- Service temperature: -0°C to +50°C.

# **TECHNICAL PROPERTIES**

Technical Property	Nominal Value	Unit	Test Method
Temperature Fusion	100 - 120	°C	-
Total Thickness	0.25	mm	AFERA 4006

# Note:

\*\*\*This will be taken from the core product for the SAP Material Group\*\*\*

Version: 12 Generated Date: 27 November 2025 Page: 1 of 2

www.scapaindustrial.com Product Code: 2900

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.

# STANDARD PRESENTATIONS

Colours: Red and White stripedCore: 76 mm cardboard core

· Packaging: Bulk

Roll Length: 100 metresRoll Width: 50 mm

# **RECOMMENDATIONS**

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from

dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between  $+10^{\circ}$ C and  $+30^{\circ}$ C. Under

these conditions, the storage life of the tape in a temperate climate will be at least one year.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.

Version: 12 Generated Date: 27 November 2025 Page: 2 of 2

www.scapaindustrial.com Product Code: 2900