



## **BARNIER ® 2953**

# Extra wide surface protection

### **DESCRIPTION**

Scapa 2953 is a two in one product: an electrostatic film strip made of polyethylene, pretaped on one side by a rubber adhesive coated cloth tape of 35mm. Scapa 2953 is transparent (film) and blue (masking tape).

#### **APPLICATIONS**

- Extra large surface protection during facade renovation.
- Interior/ exterior usage
- Wide protection against paint projections in a construction site.

### **PRODUCT BENEFITS**

- Time saving and long term protection
- Quick and simple application (2 in 1 solution)
- Good resistance to water and chemical agents.
- Extra large protection during facelift operation
- Good peel adhesion.
- Suitable for brush, roller and spray gun applications.
- · No staining.

### **TECHNICAL PROPERTIES**

Technical Property	Nominal Value	Unit	Test Method
Adhesion to Steel	14	Oz/Inch (N/25mm)	ASTM D3330
Temperature Range: Application (Ambient)	0°C - 40°C	°C	-
Thickness Film PE	0.018	mm	AFERA 5006

Version: 3 Generated Date: 02 January 2026 Page: 1 of 2

www.scapaindustrial.com Product Code: 2953

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.

### STANDARD PRESENTATIONS

Core: 25mm cardboard
Packaging: individual

• Roll Length: 18m

• Roll Width: 650mm (Tape width: 35mm)

### **RECOMMENDATIONS**

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +15°C and +25°C. Under these conditions, the storage life of the tape in a temperate climate will be at least 12 months.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.

Scapa masking tapes are not suitable for outdoor exposure and should not be submitted to prolonged periods of sunlight, as tapes may become difficult to remove. Clean removal may also vary with surface type, lacquers, primers and paints nature and the temperature of the surface at removal. For best results, remove the tape as soon as possible after applying the paints pulling it slowly at a 90° angle with constant speed.

Version: 3 Generated Date: 02 January 2026 Page: 2 of 2

www.scapaindustrial.com Product Code: 2953