



Scapa 296

Shuttering PVC Tape

DESCRIPTION

Scapa 296 is a soft PVC with a white coloured pressure sensitive rubber based adhesive system. Scapa 296 is yellow.

APPLICATIONS

- Horticultural and agricultural industries
- Floor marking
- Used for shuttering in building industries

PRODUCT BENEFITS

- Easy to tear by hand
- Temperature resistance up to 50°C
- Good unwind at low temperature
- Flexible and conformable.
- Good adhesion to dirty and wet surface

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Elongation at Break	200	%	AFERA 4005
Peel Adhesion to Steel	1.2	N/cm	AFERA 4001
Tensile Strength	29	N/cm	AFERA 4004
Total Thickness	0.158	mm	AFERA 4006

Version: 6 Generated Date: 16 December 2025 Page: 1 of 2

www.scapaindustrial.com Product Code: 296

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.

STANDARD PRESENTATIONS

Branding: Plain or SpecificPackaging: Wrap or bulk

Roll Length: 33mRoll Length: 76mm

• Roll Width: 38mm, 50mm, 75mm

RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +10°C and +25°C. Under these conditions, the storage life of the tape in a temperate climate will be at least one year.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.

Version: 6 Generated Date: 16 December 2025 Page: 2 of 2

www.scapaindustrial.com Product Code: 296