



# **Scapa 3119**

# Waterproof Cloth Tape

## **DESCRIPTION**

Scapa 3119 is a high adhesion; polyethylene laminated waterproof cloth tape, coated with a pressure sensitive rubber adhesive. Scapa 3119 is available in Orange.

#### **APPLICATIONS**

- Polyethylene coated fabric for all uses in construction
- Used for sealing, bundling, short term masking and protecting.
- Excellent for jointing polyethylene dust sheets
- Designed as a general purpose waterproof cloth tape
- Carpet joining and edging.
- Exterior and Interior usage.

# **PRODUCT BENEFITS**

- Good performance at low temperatures
- Service temperature -10°C to +60°C
- Easy and clean hand tear
- Flexible and conformable
- Excellent sealing property
- Good water resistance
- Good adhesion on rough surfaces

Version: 26 Generated Date: 12 July 2025 Page: 1 of 2

www.scapaindustrial.com Product Code: 3119

## **TECHNICAL PROPERTIES**

| Technical Property  | Nominal Value | Unit | Test Method |
|---------------------|---------------|------|-------------|
| Adhesion to Steel   | 7.5           | N/cm | AFERA 5001  |
| Elongation at Break | 15            | %    | AFERA 5004  |
| Tensile Strength    | 43            | N/cm | AFERA 5004  |
| Total Thickness     | 210           | μm   | AFERA 5006  |

#### Note:

\*\*\*This will be taken from the core product for the SAP Material Group\*\*\*

#### STANDARD PRESENTATIONS

• Colours: Orange

Packaging: Individual shrink

Packaging: 24

• Core: 76 mm in cardboard printed with Scapa

Dimension: 33mx48mm - 33mx72mm

## **RECOMMENDATIONS**

The rolls must be stored flat in their original packaging, protected from dust, light, damp and solvent fumes at a temperature between 15°C and 25°C inclusive. In these conditions the storage time in a temperate climate must not exceed 12 months. Surfaces must be clean, dry and free from dust, grease, oil or any other contaminant. Due to the diversity of materials employed by the user, tests carried out by the user himself/herself before the final application is the surest way of testing the material.

Version: 26 Generated Date: 12 July 2025 Page: 2 of 2

www.scapaindustrial.com Product Code: 3119