



BARNIER ® 6097

Plasticised PVC Adhesive Tape

DESCRIPTION

Scapa 6097 is a plasticised PVC with a cross-linked pressure sensitive rubber based adhesive. Scapa 6097 is blue (construction application), and white (automotive application).

APPLICATIONS

- · Paint masking on fragile media
- Long-lasting paint masking

PRODUCT BENEFITS

- Does not leave any residual adhesive mass even after a week
- Hand-tearable
- Very easy to unroll
- Remains conformable and pliable even in low winter temperatures
- Adheres to all media

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Adhesive strength on stainless steel	0.8	N/cm	AFERA 4001
Breaking Strength	24	N/cm	AFERA 4004
Elongation at Break	150	%	AFERA 4005
Temperature Resistance	70	°C	-
Total Thickness	0.125	mm	AFERA 4006

Version: 14 Generated Date: 19 December 2025 Page: 1 of 2

www.scapaindustrial.com Product Code: 6097

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.

STANDARD PRESENTATIONS

• Branding: Scapa/Barnier

• Mandrel: 76 mm

• Packaging: Individually wrapped in film

• Roll Length: 33 m

• Roll size: 50 mm, 75 mm

RECOMMENDATIONS

The rolls must be stored flat, in their original packaging, protected against dust, light, humidity and solvent fumes, at a temperature between +10°C and +25°C. Under these conditions, the rolls must not be stored for more than 12 months in a temperate climate.

The surfaces must be clean, dry and free of dust, grease, oil and any other contaminants

Version: 14 Generated Date: 19 December 2025 Page: 2 of 2

www.scapaindustrial.com Product Code: 6097