

BARNIER® BB350

Butyl adhesive tape

DESCRIPTION

Scapa BB350 is a water-tight sealing tape composed of a polyethylene film coated with butyl rubber and protected by a filled liner. BB350 is extra stretchy and is grey.

APPLICATIONS

- Do not expose the product directly to UV light.
- Also allows flexible or rigid pipes, ventilation channels made from aluminium, zinc-coated metal, polyethylene or rigid PVC to be sealed.
- Allows openings in roofs to be sealed (holes, air vents, chimneys).
- Allows vapour barrier films and rain barriers (partitions, walls, roofs) to be made water-tight even when they have been pierced

PRODUCT BENEFITS

- High resistance to heat up to 100°C
- Free from solvents
- Barrier to gas and vapour
- Flexible, malleable and elasticated lengthways as well as crossways so that it can be made to fit perfectly around materials with irregular dimensions.
- Excellent adhesion at low temperatures
- Can be torn by hand thanks to the protective silicon-filled system which allows the butyl to be easily detached from the protector.
- Adhesive with strong adhesive power

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Adhesive Power at 90°	>70	N	ASTM D 1000
Service Temperature	-40°C/+100°C	°C	-
Temperature During Application	+0°C/+45°C	°C	-
Tensile Strength	1000	%	EN 12311-11
Thickness	1.5	mm	-

STANDARD PRESENTATIONS

- Roll Length: 10 metres
- Roll Width: 50mm
- Thickness : 1.5mm

RECOMMENDATIONS

The rolls should be stored flat on their cut edge in their original packaging protected from dust, heat, direct sunlight, humidity and solvent fumes. Storage temperature must be kept between 5°C and 40°C. A maximum use by date of strictly 12 months from the date of manufacture is recommended.

The product must not be allowed to freeze. Surfaces to which the adhesive is to be applied must be clean, dry and free of all traces of dust, grease, oil or any other contaminating agent.