



Page: 1 of 2

BARNIER ® FR102

General Purpose Double Sided Cloth Tape

DESCRIPTION

Barnier 102 is a general purpose double sided tape based on a cotton cloth. The tape is coated on both sides with a synthetic rubber based hot melt system, with an 80g/m2 light brown siliconised paper release liner, resulting in a total thickness of 0.215mm. Recommended for a variety of bonding and fixing applications.

APPLICATIONS

- Permanent carpet fixing.
- Permanent floor covering fixing.
- Suitable for general purpose thick bonding and mounting applications.

PRODUCT BENEFITS

- High peel adhesion.
- Hand tearable.
- Mattress effect for rough or uneven surfaces.
- Service temperature: -10°C up to +50°C (withstands shorter periods up to 65°C).

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
180° Peel Adhesion	14	N/cm	AFERA 5001
Elongation at Break	4	%	AFERA 5004
Liner Thickness	0.07	mm	AFERA 5006
Static Sheer	>4	Hours	AFERA 5012
Tape Thickness (Without Liner)	215	Microns	AFERA 5006
Tensile Strength	12	N/cm	AFERA 5004

Version: 21 Generated Date: 20 December 2025

www.scapaindustrial.com Product Code: FR102

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.

Note:

This will be taken from the core product for the SAP Material Group

STANDARD PRESENTATIONS

• Colours: White

• Packaging: 16 rolls; 24 rolls

• Dimension: 10mx50mm; 25mx50mm

RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +10°C and +30°C. Under these conditions, the storage life of the tape in a temperate climate will be at least one year.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminant.

Version: 21 Generated Date: 20 December 2025 Page: 2 of 2

www.scapaindustrial.com Product Code: FR102