

## BARNIER® 0485

### Rubber Resin Adhesive Strip

#### DESCRIPTION

Scapa 0485 is a solvent free rubber resin based hot melt adhesive. Scapa 0485 is available in amber in a strip format supplied on an easily removable paper liner.

#### APPLICATIONS

- Fixing on different materials: metal, wood, rigid plastics, polypropylene
- Collage on skirting boards, paneling, decorative rods, sill bars and electrical accessories (junction boxes, chutes)
- Polyane sheet connection in construction
- Maintaining parts before fixing deifnitive

#### PRODUCT BENEFITS

- Clean and easy application
- Excellent adhesive power
- Solvent-free adhesive

#### TECHNICAL PROPERTIES

| Technical Property              | Nominal Value | Unit              | Test Method |
|---------------------------------|---------------|-------------------|-------------|
| Cohesion                        | 0.6           | N/mm <sup>2</sup> | 55270*      |
| Service Temperature             | 0 - 40        | °C                | -           |
| Softening Point (Ring and Ball) | 85            | °C                | 55272*      |
| Specific Gravity                | 0.98          | g/cm <sup>3</sup> | 55295*      |
| Tack (Rolling Ball Method)      | 30            | mm                | 55233*      |

*Note:*

*\* Scapa Internal Test Method.*

*Note: should not be used where good chemical or UV resistance is required.*

## **STANDARD PRESENTATIONS**

- Dimension : 10mx19mm
- Packaging: 6
- Core: 76mm plain

*Note:*

*Note: Information on stock items, non-standard sizes, and lead times is available on request*

## **RECOMMENDATIONS**

It is recommended that this product is applied at temperatures over 10°C.

To aid the cutting of 0485, it is advisable to dip blades or scissors into water immediately prior to use. The rolls should be stored flat on their cut edges in the original packaging, until required for use. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Service life will vary with conditions of use and is affected by climatic environment, but should not be less than one year from date of manufacture, if stored in a moderate climate and good conditions.