BARNIER®
www.barnierpro.com

Technical DATA

BARNIER ® 1500

Glass Grid Adhesive Tape

DESCRIPTION

Scapa 1500 is a glass grid tape coated with a rubber adhesive. Scapa 1500 is available in white.

APPLICATIONS

- Splicing plasterboard with thinned edges and repairing holes or cracks on walls
- Do not use on the ceiling
- Not suitable for corner joints

Note:

NOTE: DO NOT USE ON THE CEILING

PRODUCT BENEFITS

- Avoids the implementation of a first coating pass
- Easy to install, do not tear, do not fold. Allows clean work without bubbles or cracks on the joint
- To be used preferably indoors, has a good adhesion on the paper of coating of the plates of plasters
- Its use must be associated with a ready-to-use or powdered paste sealant. To spoil: the filler must be flexible and non-fluid

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Elongation at Break	5	%	AFERA 4005
Tensile Strength	90	N/cm	AFERA 4004
Total Thickness	0.20	mm	AFERA 4006

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.

Note:

****This will be taken from the core product for the SAP Material Group****

STANDARD PRESENTATIONS

- Core: 76mm
- Packaging: Individually film wrapped
- Roll Length: 45m, 153m
- Roll Width: 48mm

Note:

Note: Information on stock items, non-standard sizes, and lead times is available on request

RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging at a temperature between +10°C and +30°C until required for use.

The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Surfaces should be clean, dry and free of dust, grease, oil or other contaminants Service life will vary with conditions of use and is affected by climatic environment, but it is recommended that the product should be used within 24 months of date of manufacture, if stored in good conditions

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.