BARNIER®
www.barnierpro.com

Technical DATA

# BARNIER ® 2425

Anti Slip Tape

## DESCRIPTION

Scapa 2425 is a self-adhesive ant-slip material. It is made of a plastic film on which aluminium oxide particles are hold in place by a polymer resin. On the other side an acrylic based adhesive is protected by a siliconized paper liner.

## APPLICATIONS

- Securing stairs, slippery surfaces
- Securing industrial surfaces
- Resists many pedestrian passages and light vehicles

## PRODUCT BENEFITS

- Inside/outside
- If applied correctly, adhere to most of the surface
- High grip = high level of coefficient of friction.
- Hand tearable
- If applied correctly, resistant to oil, water and most of chemicals in commercial environments.

## TECHNICAL PROPERTIES

| Technical Property | Nominal Value | Unit | Test Method |
|---|---|---|---|
| Total Thickness | 700 | µm | AFERA 5006 |
| Peel Adhesion on Steel | 6 | N/cm | AFERA 5001 |
| Tensile Strength | 28 | N/cm | AFERA 5004 |
| Elongation at Break | 50 | % | AFERA 5004 |
| Temperature Resistance | -30 / +70 | °C | - |



This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.

## STANDARD PRESENTATIONS

- Branding: Barnier
- Roll Length: 18 m
- Roll Width: 25 / 50 mm
- Colours: Black, Yellow/Black

## RECOMMENDATIONS

The rolls should be stored flat, in their original packaging, protected against dust, light, moisture and solvent fumes, and at a temperature between +10°C and +30°C. Under these conditions, the period of storage of the rolls in a temperate climate may not exceed 24 months. Surfaces should be clean, dry and free of dust, grease, oil and or other contaminants. Owing to the variety of materials used by the user, a test carried out by the user themselves constitutes the most reliable way of testing the material before its actual application.
For porous surfaces, it is recommended to use an isopropyl alcohol (IPA)-based cleaner and a solvent-based or water-based primer for better adhesion.



This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.