BARNIER ® 2951

Wide surface protection

DESCRIPTION

Scapa 2951 is a two in one product: an electrostatic film strip made of polyethylene, pretaped once one side by a rubber adhesive coated cloth tape. Scapa 2951 is transparent (film) and blue (masking tape).

APPLICATIONS

- Interior/ exterior usage.
- Ideal for outdoor protection where high stability is required

PRODUCT BENEFITS

- Neat and clean Edges
- Quick and simple application (2 in 1 solution)
- Transparent electrostatic film that allows immediate adhesion to windows, etc.
- The electrostatic and high density allows immediate adhesion on windows etc...and avoids drippings
- Good peel adhesion.
- No staining.
- Good adhesion on most difficult surfaces.

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Adhesion to Steel	3.8	N/cm	ASTM D3330
Temperature Resistance	-10°C à +70°C	°C	-
Thickness Film PE	0.015	mm	AFERA 5006
Thickness of Tape	0.3	mm	AFERA 5006

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.

Note:

****This will be taken from the core product for the SAP Material Group****

STANDARD PRESENTATIONS

- Packaging: Individuel
- Roll Length: 20m ; (adhesive width : 19mm. Color : blue)
- Roll Width: 550mm ; 1100mm ; 1600mm ; 2300mm

RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +10°C and +30°C.
Under these conditions, the storage life of the tape in a temperate climate will be at least 12 months.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.

Scapa masking tapes are not suitable for outdoor exposure and should not be submitted to prolonged periods
of sunlight, as tapes may become difficult to remove. Clean removal may also vary with surface type, lacquers, primers and paints nature and the temperature of the surface at removal. For best results, remove the tape as soon as possible after applying the paints pulling it slowly at a 90°angle with constant speed.

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.