Scapa 3115

Waterproof Cloth Tape UV Resistant

DESCRIPTION

Scapa 3115 is a high adhesion; polyethylene laminated waterproof cloth tape, coated with a pressure sensitive rubber adhesive. UV resistance, clean removal up to 60 days outside. Scapa 3115 is available in white.

APPLICATIONS

- Polyethylene coated fabric for all uses in construction
- Suitable for various surfaces
- Exterior and indoor usage
- Used for sealing, bundling, masking and protecting
- Excellent for jointing polyethylene dust sheets

PRODUCT BENEFITS

- UV resistance
- Clean removal without residue after 60 days on PVC, painted aluminium, brick surfaces and 30 days on concrete surfaces
- Strong polyethylene fabric tape
- Very good initial adhesion
- Good adhesion on flat and rough surfaces
- Good water resistance
- Easy tearing by hand
- Flexible and adaptable to different surfaces
- Good performance at low temperature

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Temperature Resistance	-10 to +60	°C	-
Adhesion to Steel	8	N/cm	AFERA 5001
Elongation at Break	15	%	AFERA 5004
Tensile Strength	40	N/cm	AFERA 5004
Total Thickness	210	µm	AFERA 5006

STANDARD PRESENTATIONS

- Branding: Scapa
- Packaging: Individual shrink with barcode label
- Core: 76mm
- Roll Length: 33m
- Roll Width: 48mm
- Colours: White

RECOMMENDATIONS

Not suitable for marble surfaces.
The rolls must be stored flat in their original packaging, protected from dust, light, damp and solvent fumes at a temperature between 15°C and 25°C inclusive. In these conditions the storage time in a temperate climate must not exceed 12 months. Surfaces must be clean, dry and free from dust, grease, oil or any other contaminant. Due to the diversity of materials employed by the user, tests carried out by the user himself/herself before the final application is the surest way of testing the material.

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.