BARNIER®
www.barnierpro.com

Technical DATA

Scapa 3119

Waterproof Cloth Tape

DESCRIPTION

Scapa 3119 is a high adhesion; polyethylene laminated waterproof cloth tape, coated with a pressure sensitive rubber adhesive. Scapa 3119 is available in Orange.

APPLICATIONS

- Polyethylene coated fabric for all uses in construction
- Used for sealing, bundling, short term masking and protecting.
- Excellent for jointing polyethylene dust sheets
- Designed as a general purpose waterproof cloth tape
- Carpet joining and edging.
- Exterior and Interior usage.

PRODUCT BENEFITS

- Good performance at low temperatures
- Service temperature -10°C to +60ºC
- Easy and clean hand tear
- Flexible and conformable
- Excellent sealing property
- Good water resistance
- Good adhesion on rough surfaces

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Adhesion to Steel	7.5	N/cm	AFERA 5001
Elongation at Break	15	%	AFERA 5004
Tensile Strength	43	N/cm	AFERA 5004
Total Thickness	210	µm	AFERA 5006

Note:

****This will be taken from the core product for the SAP Material Group****

STANDARD PRESENTATIONS

- Colours: Orange
- Packaging: Individual shrink
- Packaging: 24
- Core: 76 mm in cardboard printed with Scapa
- Dimension : 33mx48mm - 33mx72mm

RECOMMENDATIONS

The rolls must be stored flat in their original packaging, protected from dust, light, damp and solvent fumes at a temperature between 15°C and 25°C inclusive. In these conditions the storage time in a temperate climate must not exceed 12 months. Surfaces must be clean, dry and free from dust, grease, oil or any other contaminant. Due to the diversity of materials employed by the user, tests carried out by the user himself/herself before the final application is the surest way of testing the material.

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.