# BARNIER ® 9060WS

60°C Washi precision masking tape for fragile surfaces

## DESCRIPTION

Precision Japanese Washi masking tape for delicate surfaces. Scapa 9060WS is uniformly coated with an acrylic adhesive system. Ideal for precision paintwork on very fragile surfaces. For interior use

## APPLICATIONS

- Masking with a fine line boundary when painting.
- Masking tape for multiple layer paint jobs (various layers of different colours of paint) whereby there is
- no built up of paint
- For perfect colour separation
- Significantly reduces the risk of colours overlapping thanks to its ultra-thin surface
- Professional masking tape for painters and plasterers in the construction and industry (for interior use)
- Suitable for use with painting by brush or spray gun with drying at room temperature
- Suitable for use with painting by brush or spray gun with drying at room temperature

## PRODUCT BENEFITS

- Resistant to damp, chemical products, lacquers and light solvents
- Does not stain
- Excellent paint flake resistance.
- Excellent shear and holding strength
- Unrolls easily and in a controlled way
- Clean removal at room temperature
- Strong adhesion to slightly difficult surfaces
- Can be used with all types of paints and varnishes



This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.

## TECHNICAL PROPERTIES

| Technical Property | Nominal Value | Unit | Test Method |
|---|---|---|---|
| Total Thickness | 75 +/- 10 | µm | DQP 7098 |
| Adhesion on Steel | > 0.9 | N/cm | AFERA 5001 |
| Tensile Strength | > 25 | N/cm | AFERA 5004 |
| Elongation at Break | > 3 | % | AFERA 5004 |

## STANDARD PRESENTATIONS

- Roll Length: 50 m
- Roll Width: 19, 25, 30, 38, 50 mm
- Packaging: Individual
- Spool : 76 mm in cardboard printed with BARNIER
- Colours: Purple

## RECOMMENDATIONS

The rolls must be stored flat in their original packaging, protected from dust, light, damp and solvent fumes at a temperature between 15°C and 25°C inclusive. In these conditions the storage time in a temperate climate must not exceed 12 months.
Surfaces must be clean, dry and free from dust, grease, oil or any other contaminant.
Due to the diversity of materials employed by the user, tests carried out by the user himself/herself before the final application is the surest way of testing the material.



This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.