Scapa FR335

High Performance, Strong Aluminium Foil Tape - 50 micron

DESCRIPTION

Scapa 335 is a 50µ soft aluminium foil coated with an acrylic adhesive system, using a siliconised paper release liner.

APPLICATIONS

- Closing rigid air duct insulation.
- For use as a heat reflector.
- Applications requiring detection by photoelectric equipment.

PRODUCT BENEFITS

- Temperature resistance: -35°C to +120°C
- Very soft and very conformable.
- Easy to tear.
- Same aluminium appearance as air duct.

Accreditation:

Meets the fire resistant requirements of specifications NF P 92 – 501, Fire Class M1, BS476 Part 6 & 7 Category 1, Class O and DIN4102-A2

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Adhesion to Steel	6	N/cm	AFERA 5001
Elongation at Break	3	%	AFERA 5004
Tensile Strength	30	N/cm	AFERA 5004
Total Thickness	90	Microns	AFERA 5006

STANDARD PRESENTATIONS

- Core: Scapa, Barnier
- Packaging: Bulk pack with interleaving.
- Roll Length: 50m
- Roll Width: 50, 75, 100mm

RECOMMENDATIONS

Rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. The storage temperature should be between +10°c and +25°C. Under these conditions, the storage life of the tape in a temperate climate will be at least 12 months.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.